

R&S® ZV-Z36 Calibration Kit Specifications



75 Years of
Driving
Innovation


ROHDE & SCHWARZ

Specifications

Specifications apply under the following conditions: 30 minutes warm-up time at ambient temperature, specified environmental conditions met, calibration cycle adhered to, and all internal automatic adjustments performed. "Typical values" are designated with the abbreviation "typ." These values are verified during the final test but are not assured by Rohde & Schwarz. "Nominal values" are design parameters that are not assured by Rohde & Schwarz. These values are verified during product development but are not specifically tested during production.

Rohde & Schwarz equipment is designed for reliable operation up to an altitude of 3000 m above sea level, and for transport up to an altitude of 4500 m above sea level.

Measurement range

| | | |
|-----------------|--|-------------------------------|
| Connectors | | 2.4 mm female and 2.4 mm male |
| Impedance | | 50 Ω |
| Frequency range | | 0 Hz to 50 GHz |

Effective system data

The specified effective system data are established after performing a suitable system error calibration, e.g. TOSM, at a vector network analyzer R&S®ZVA, R&S®ZVB, or R&S®ZVT, using the characteristic data of the calibration kit, which are stored on a provided USB-stick. This data is valid between +18 °C and +28 °C, at a measurement bandwidth of 10 Hz, and a nominal power of –10 dBm at the calibration ports. The calibration kit is fully functional down to 0 Hz, with effective system data as specified below, although the data is only verified for frequencies as stated.

| | | |
|-----------------------|-------------------|-----------------------|
| Directivity | 10 MHz to 700 MHz | >30 dB, typ. 40 dB |
| | 700 MHz to 24 GHz | >40 dB, typ. 46 dB |
| | 24 GHz to 50 GHz | >30 dB, typ. 36 dB |
| Source match | 10 MHz to 700 MHz | >30 dB, typ. 40 dB |
| | 700 MHz to 24 GHz | >34 dB, typ. 40 dB |
| | 24 GHz to 50 GHz | >26 dB, typ. 36 dB |
| Reflection tracking | 10 MHz to 700 MHz | <0.3 dB, typ. 0.1 dB |
| | 700 MHz to 24 GHz | <0.3 dB, typ. 0.1 dB |
| | 24 GHz to 50 GHz | <0.3 dB, typ. 0.2 dB |
| Load match | 10 MHz to 700 MHz | >30 dB, typ. 40 dB |
| | 700 MHz to 24 GHz | >30 dB, typ. 36 dB |
| | 24 GHz to 50 GHz | >26 dB, typ. 33 dB |
| Transmission tracking | 10 MHz to 700 MHz | <0.2 dB, typ. 0.1 dB |
| | 700 MHz to 24 GHz | <0.1 dB, typ. 0.05 dB |
| | 24 GHz to 50 GHz | <0.3 dB, typ. 0.2 dB |

General data

| | | |
|------------------------|-------------------------------|--|
| Temperature loading | operating temperature range | +18 °C to +28 °C |
| | permissible temperature range | 0 °C to +50 °C |
| | storage temperature range | -40 °C to +70 °C |
| | | in line with IEC 60068-2-1 and IEC 60068-2-2 |
| Calibration interval | | 1 year |
| Dimensions (W x H x D) | | 336 mm x 66 mm x 270 mm |
| | | 13.2 in x 2.6 in x 10.6 in |
| Weight | | 1400 g (3 lb) |
| Shipping weight | | 4 kg (9 lb) |

Ordering information

| Designation | Type | Order No. |
|--|------------|--------------|
| Calibration Kit 2.4 mm, 0 Hz to 50 GHz | R&S®ZV-Z36 | 1305.5900.02 |

Service you can rely on

- | In 70 countries
- | Person-to-person
- | Customized and flexible
- | Quality with a warranty
- | No hidden terms

Regional contact

Europe, Africa, Middle East

+49 1805 12 42 42* or +49 89 4129 137 74

customersupport@rohde-schwarz.com

North America

1-888-TEST-RSA (1-888-837-8772)

customer.support@rsa.rohde-schwarz.com

Latin America

+1-410-910-7988

customersupport.la@rohde-schwarz.com

Asia/Pacific

+65 65 13 04 88

customersupport.asia@rohde-schwarz.com

Rohde & Schwarz GmbH & Co. KG

Mühlendorfstraße 15 | 81671 München

Phone +498941 290 | Fax +498941 29 121 64

www.rohde-schwarz.com

R&S® is a registered trademark of Rohde & Schwarz GmbH & Co. KG

Trade names are trademarks of the owners | Printed in Germany (as)

PD 5213.9405.22 | Version 01.00 | July 2008 | R&S®ZV-Z36

Subject to change

*0.14 €/min within German wireline network; rates may vary in other networks (wireline and mobile) and countries.